

# SS-28/212/215/315/2152

**interM**

## SOUND REINFORCEMENT SPEAKER SYSTEM



### FEATURES

- High-Classed unit for disco club, concert hall and gymnasium.
- As 2way, 3way Full range system distortion improved at powerfull sound.
- Trapezoidal type with portable enclosure.
- Designed as high frequency driver for compact sound system.

### SPECIFICATIONS

|                    |        | Unit | SS-28                 | SS-212                        | SS-215                        | SS-315                        | SS-2152                       |
|--------------------|--------|------|-----------------------|-------------------------------|-------------------------------|-------------------------------|-------------------------------|
| Rated Output       | Normal | W    | 150                   | 300                           | 400                           | 400                           | 800                           |
|                    | Peak   | W    | 375                   | 800                           | 1000                          | 1000                          | 2000                          |
| Frequency Response | Hz     |      | 60-18k                | 54-20k                        | 50-20k                        | 50-20k                        | 38-20k                        |
| Impedance          | Ω      |      | 8                     | 8                             | 8                             | 8                             | 4                             |
| S.P.L              | 1m/1W  | dB   | 97                    | 100                           | 101                           | 101                           | 100                           |
| HF Driver          | Inch   |      | 1" COMPRESSION DRIVER | 2 TITANIUM COMPRESSION DRIVER | 2 TITANIUM COMPRESSION DRIVER | 2 TITANIUM COMPRESSION DRIVER | 2 TITANIUM COMPRESSION DRIVER |
| LF Driver          | Inch   |      | 8" CONE WF            | 12" CONE WF                   | 15" CONE WF                   | 15" CONE WF                   | 15" CONE WF ×2                |
| Dispersion         | Angel  |      | 90°(H) ×60°(V)        | 90°(H) ×60°(V)                | 120°(H) ×90°(V)               | 90°(H) ×60°(V)                | 120°(H) ×90°(V)               |
| Cross-Over FREQ    | Hz     |      | 3k                    | 1.8k                          | 1.8k                          | 800, 3.5k                     | 1.8k                          |
| Weight             | kg     |      | 12.5                  | 25                            | 32                            | 39                            | 55                            |
| Dimensions(W×H×D)  | mm     |      | 325 ×520 ×290         | 435 ×692 ×406                 | 485 ×785 ×457                 | 485 ×785 ×457                 | 537 ×1245 ×466                |

**interM**

OFFICE : 653-5 BANGHAK-DONG, DOBONG-KU, SEOUL, KOREA TEL : 82-2-2289-8140~8, FAX : 82-2-2289-8149

Home page : <http://www.inter-m.com>

E-mail : [export@inter-m.com](mailto:export@inter-m.com)

9047928110 C