

# PDG-DSU20

SVGA Ultraportable Multimedia Projector



### ULTRA-COMPACT, FULLY PORTABLE SVGA DESIGN

Not much larger than a laptop PC, the PDG-DSU20 weighs less than 6.5 pounds and delivers true SVGA picture quality in a versatile, go-anywhere system.

### HIGH BRIGHTNESS and CONTRAST

With brightness level of 2000 ANSI Lumens and a contrast ratio of 2000:1 make this projector a winner in its category.

### F2.51-2.69 ZOOM LENS

Comes with its own 1:1.1 zoom lens, which can throw a crisp, bright 100" diagonal image.

### AUTO INPUT SEARCH

Searches, finds and displays incoming source material automatically.

### SPECIAL FEATURES

Component input, quiet fan operation and versatile go anywhere capability make this a truly portable projector. Also may be ceiling or inverse mounted for enhanced versatility.



DLP® and the DLP logo are registered trademarks of Texas Instruments..

# SANYO

PRESENTATION TECHNOLOGIES

21605 Plummer Street  
Chatsworth, CA 91311  
Ph: 888-337-1215 (toll-free)  
Fax 818.717.2719  
www.sanyolcd.com

## TENTATIVE Specifications

Resolution	SVGA (800 x 600)
Brightness	2000 ANSI Lumens
Uniformity	85% (corner to center)
LCD Panel System	0.55" DMD x 1
Number of Pixels	480,000(800 x 600)
Contrast Ratio	2000:1
Image Size (diagonal)	27.8" – 255"
Aspect Ratio	4:3
Throw Distance	3.9' – 32.8"
Zoom/Focus	Manual
Zoom Ratio	1:1.1
Up/Down Ratio	13.3:-1
Digital Keystone Correction	Vertical: +/- 15° MAX
Projection Lens	F2.51-2.69/f0.86"-0.98"
Lens Throw Ratio	1.95-2.15:1
Projection Lamp	180W UHP
Scanning Frequency	H Sync: 31-79kHz, V Sync: 50-85Hz
Dot Clock	25-135MHz
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NTSC4.43
Computer Compatibility	SVGA, XGA, <b>SVGA</b> , VGA
Sound Output	One-piece, 2-watt Mono
Voltage	100-240V AC (auto Voltage) ; 50/60 Hz
BTU Rating	853
dB Rating	T.B.A
Power Consumption	250W
Dimensions (WxHxD)	10.84" x 3.4" x 8.72" (not including Adjustable Feet & Lens Part)
Net Weight	6.5lbs
User Maintenance	replace lamp assembly
PC Input Terminals	D-Sub15 x 1
Video Input Terminals	Composite Video (RCA x 1) • S-Video (Mini-DIN 4-pin) • Audio(stereo mini-jack : common)
Control Terminals	• USB (Type B)
Included Accessories	Wireless remote • CR2025 batteries • Owner's Manual • VGA Cable • Lens Cap with strap • Soft Carrying Bag • AC power supply code
Optional Accessories	• POA-CA-COMPVGA – Component– VGA conversion Cable • 610 337 1764 – Replacement Lamp
Service Port	n/a
Warranty	Three years parts and labor; 90 days original lamp; Quick Repair Program under warranty

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

