

SPECIFICATION

Model	QSM-624EZ
Power Output (RMS)	240W
Power Supply	AC 115/230AC 50/60Hz DC24V
Frequency Response	50Hz to 20KHz \pm 3dB
Total Harmonic Distortion	\leq 1% @ 1KHz
Signal To Noise Ratio	86dB
Sensitivity	XLR (balanced)
	Channel 1 ~3 (mic 1 ~ 3) 1mV @ 600 ohm
	Tel (terminal) 100mV @ 600 ohm
	Channel 4 (mic 4) 0.5mV @ 600 ohm
	AUX 1 (RCA) 100mV @ 22K ohm
	Channel 5 (mic 5) 100mV @ 600 ohm
	AUX 2 (RCA) 100mV @ 22K ohm
	AUX 3 (RCA) 100mV @ 22K ohm
	Tape out (RCA), AUX out (RCA) 1V @ 150K ohm
Output	8 ohm 70V / 100V
Chime Input	Mic 5
Voice Priority Mute	Mic 1
Phantom Power Adjustable	Mic 1 ~ 5
Tone	Bass: 100Hz \pm 10dB Treble: 10Khz \pm 10dB
AC Power Consumption @ Rated Power	640W
DC Power Consumption @ Rated Power	15A
Dimension	88(H) x 425(W) x 305(D) mm
Weight	11.5Kg
Mounting	Free Standing or 19" Rack